

SYMBOL	OPIS PRODUKTU W ORYGINALE	CENA w EUR netto
<b>Analog Two-Way Bi-Amplified Active Monitors</b>		
6010 APM	Compact, Two-Way Active Loudspeaker. Solid die-cast aluminium MDE™ cabinet (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 76 mm (3") LF and 19 mm (.75") HF drive units. RCA input corrector. Integrated crossover and amps -12W and 12W. Room response controls on rear panel. On-Off and volume control on the back panel. 3/8" mic stand thread. Integrated M6 mounting threads and VESA 75mm M4 in the back. Wall mount bracket included. Iso-Pod™ table support included. Matt black painted finish.	178,54
6010 ASM	As 6010 APM above but in silver painted finish	178,54
6010 AWM	As 6010 APM above but in white painted finish	178,54
6010 AZM	As 6010 APM above but in hand polished aluminium finish	267,02
8020 APM	Compact, Two-Way Active Nearfield Monitor. Solid die-cast aluminium MDE™ cabinet (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 100 mm (4") LF and 19 mm (.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 20W and 20W. Room response controls on rear panel. On-Off and volume control in one on the front. 3/8" mic stand thread. Integrated M6 mounting threads in the back. Wall mount bracket included. Iso-Pod™ table support included. Matt black painted finish.	273,34
8020 ASM	As 8020 APM above but in silver painted finish	293,88
8020 AWM	As 8020 APM above but in white painted finish	293,88
8020 AZM	As 8020 APM above but in hand polished aluminium finish	674,66
8030 APM	Compact, two way Active Nearfield Monitor. Solid die-cast aluminium MDE cabinet (Minimum Diffraction Enclosure) including DCW protection grills and magnetically shielded, 130mm (5") LF and 19mm (0.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 40 W and 40 W. Room response controls on rear panel. On-Off and volume control on the front. 3/8" mic stand thread. Integrated Omnimount 20.5WA or CA mounting threads in the back. Iso-Pod table support included. Matt black painted finish.	413,96
8030 ASM	As 8030 APM above but in silver painted finish	431,34
8030 AWM	As 8030 APM above but in white painted finish	431,34
8030 AZM	As 8030 APM above but in hand polished aluminium finish	936,94
8130 AP	Compact, Two-Way Digital Input Active Monitor. As 8030APM but with AES/EBU Digital input combined with analogue input XLR connector. Solid die-cast aluminium MDE cabinet (Minimum Diffraction Enclosure) including DCW protection grills and magnetically shielded, 130mm (5") LF and 19mm (0.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 40 W and 40 W. Room response controls on rear panel. On-Off and volume control on the front. 3/8" mic stand thread. Integrated Omnimount 20.5WA or CA mounting threads in the back. Iso-Pod table support included. Matt black painted finish.	597,24
8040 APM	Two way Active Nearfield Monitor. Solid die-cast aluminium MDE cabinet (Minimum Diffraction Enclosure) including DCW protection grills and magnetically shielded, 165mm (6.5") LF and 19mm (0.75") HF drive units. Balanced XLR connector. Integrated crossover and amps - 90 W and 90 W. Integrated Omnimount 20.5WA or CA and K&M 24180 mounting threads in the back. M10 stand thread in bottom. Room response controls on rear panel. Iso-Pod table support included. Matt black painted finish.	663,60
8040 AWM	As 8040 APM above but in white painted finish	695,20
8040 AZM	As 8040 APM above but in hand polished aluminium finish	1 341,42

SYMBOL	OPIS PRODUKTU W ORYGINALE	CENA w EUR
8050 APM	Two way Active Nearfield Monitor. Solid die-cast aluminium MDE cabinet (Minimum Diffraction Enclosure) including DCW protection grills and magnetically shielded, 205mm (8") LF and 25mm (1") HF drive units. Balanced XLR connector. Integrated crossover and amps - 150 W and 120 W. Integrated Omnimount 20.5WA or CA mounting threads in the back. M10 stand thread in bottom. Room response controls on rear panel. Iso-Pod table support included. Matt black painted finish.	1 079,14
8050 AWM	As 8050 APM above but in white painted finish	1 134,44
8050 AZM	As 8050 APM above but in hand polished aluminium finish	2 129,84

### DSP Two-Way Bi-Amplified Active Monitors

8240 APM	DSP Bi-amplified Monitor System. Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ and magnetically shielded 165 mm (6.5") LF and 19 mm (3/4") HF drive units. Integrated crossover and amplifiers – 90 W and 90 W. Balanced analog XLR input connector and digital AES/EBU In and Thru XLR connectors. Dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Controls for Stand-Alone operational mode on rear panels. Integrated rear M6 mounting threads. Iso-Pod™ table support included. Matt black painted finish.	954,32
8250 APM	DSP Bi-amplified Monitor System. Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ and magnetically shielded 205 mm (8") LF and 25 mm (1") HF drive units. Integrated crossover and amplifiers – 150 W and 120 W. Balanced analog XLR input connector and digital AES/EBU In and Thru XLR connectors. Dual Genelec Loudspeaker Manager™ (GLM™). Control Network connectors. Controls for Stand-Alone operational mode on rear panels. Integrated rear M6 mounting threads. Iso-Pod™ table support included. Matt black painted finish.	1 385,66

### Two-Way Bi-Amplified Active Monitors

1032 APM	Two way Active Near Field Monitor, Magnetically shielded 250mm (10") LF 25mm (1") HF drive units. Integrated crossover and amps, 180W and 120W. EQ controls on rear panel. Durable black painted "Producer" finish. THX ® pm3 certified.	1 414,10
1032 AM	As 1032APM but with black veneer finish. THX ® pm3 certified.	1 414,10

### Three-Way Tri-Amplified Active Monitors

1037 CEM	Three-way Active Mid Field Monitor, Magnetically shielded 300mm (12") LF, GENELEC 130mm (5") MF and 25mm (1") HF drive units. Integrated crossovers and amps, 180W, 120W and 120W. Tone controls on rear panel. Black veneer finish. THX ® pm3 certified.	2 877,18
1037 CPM	As 1037B but with durable black painted "Producer" finish. THX ® pm3 certified.	2 883,50
1038 BEM	Three-way Active Mid Field Monitor, 15" LF, GENELEC 130mm (5") MF and 25mm (1") HF drive units. Integrated crossovers and amps, 400W, 120W, and 120W. Tone controls on rear panel. Black veneer finish. THX ® pm3 certified.	4 136,44
1038 BPM	As 1038BEM but with durable black painted "Producer" finish. THX ® pm3 certified.	4 144,34

SYMBOL	OPIS PRODUKTU W ORYGINALE	CENA w EUR netto
1038 BCPM-VL	Center channel three-way Active Mid Field Monitor, Magnetically shielded Dual 10" LF, GENELEC 130mm (5") MF, 25mm (1") HF drive units. System includes speaker enclosure in durable black painted "Producer" finish, a single 19" electronics with crossovers, tone controls and amplifier modules. THX ® pm3 certified. Amplification: 400W, 120W, 120W. 10m cable included.	4 657,84
1038 BCPM-VR		4 657,84
1038 BCPM-HU		4 657,84
1038 BCPM-HD		4 657,84

### Main Control Room Active Monitors

1034 BM-VU	Three-way Main Control Room Active Monitor. Soffit mount design. Magnetically shielded, dual 12" LF, GENELEC 5" MF, and 25 mm (1") HFdrive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with cross-overs, room response controls and amplifier modules. Amplification 2 x 400W, 350W, and 120W per amp module. 10 m cable included as standard.	7 414,94
1034 BM-VD		7 414,94
1034 BM-HL		7 414,94
1034 BM-HR		7 414,94

1034 BCM-VL	Center channel three- way Active Monitor System for soffit. Magnetically shielded Dual 300mm (12") LF, GENELEC 130mm (5") MF, 25mm (1") HF drive units. Amplification 400W, 350W, 120W. EQ controls on remote amp panel. System includes 1 speaker enclosure in black painted veneer finish, a single 19" remote electronics unit and 10m cables. Matches the 1034B Main Control Room Monitor Systems.	7 966,36
1034 BCM-VR		7 966,36
1034 BCM-HU		7 966,36
1034 BCM-HD		7 966,36

1039 AM-VU	Three-way Main Control Room Active Monitor. Soffit mount design. Magnetically shielded, dual 385 mm (15") LF, GENELEC 130 mm (5") MF, and 25 mm (1") HF drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 2 x 400W, 350W, & 120W per amp module. 10 m cable included as standard.	8 451,42
1039 AM-VD		8 451,42
1039 AM-HL		8 451,42
1039 AM-HR		8 451,42

1035 B-VU	Three-way Main Control Room Active Monitor System for large control rooms, soffit mount design. Dual 385mm (15") LF, Dual GENELEC 130mm (5") MF and 25mm (1") HF compression drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 2 x 1100W, 300W (3.1kW) per channel. 10 m cable included as standard.	22 582,94
1035 B-VD		22 582,94
1035 B-HL		22 582,94
1035 B-HR		22 582,94

1036 A-VU	Three-way Main Control Room Active Monitor System for large control rooms, soffit mount design. Dual 460mm (18") LF, Dual GENELEC 130mm (5") MF and 25mm (1") HF compression drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 2 x 1100W, 600 W and 300W (3.1kW) per channel. 10 m cable included as standard.	24 148,72
1036 A-VD		24 148,72
1036 A-HL		24 148,72
1036 A-HR		24 148,72

### Active Analog Subwoofer Systems

5040 APM	Active Subwoofer. Deep drawn steel cabinet with optimized reflex port, design to support up to 5 pcs. of 6010 A. System volum included. Single 165mm (6,5") magnetically shielded long throw cone driver to produce up to 98 dB SPL in half space. RCA in and output connectors. 40W amplifier with very low THD and IM distortion.	355,50
5040 ASM	As 5040 APM above but in silver painted finish	355,50
5040 AWM	As 5040 APM above but in white painted finish	355,50
7050 BP	Active Subwoofer featuring the new Genelec Lamina Spiral Enclosure™ (LSE™) bass reflex cabinet and 5.1 channel Bass Management system. Single 8" magnetically shielded long throw cone driver to produce up to 100 dB SPL in half space. 70 W amplifier with very low THD and IM distortion.	669,92

SYMBOL	OPIS PRODUKTU W ORYGINALE	CENA w EUR netto
7060 BP	Active Subwoofer featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 6.1 channel Bass Manager. Single 210 mm (10") magnetically shielded long throw cone driver to produce up to 108 dB SPL in half space. 120 W amplifier with very low THD and IM distortion. Driver overload protection and power-on signal muting. Sum out to enable coupling of two or more subwoofers for increased SPL.	1 294,02
7070 APM	Active Subwoofer featuring the new Genelec Laminar Spiral Enclosure (LSE) bass reflex cabinet and highly configurable 6.1 channel Bass Manager. Single 12" magnetically shielded long throw cone driver to produce up to 112 dB SPL in half space. 250 W amplifier with very low THD and IM distortion. Driver overload protection and power-on signal muting. SUM OUT to enable coupling two or more subwoofers for increased SPL.	1 782,24
7071 APM	Active Subwoofer featuring the new Genelec Laminar Spiral Enclosure (LSE) bass reflex cabinet and highly configurable 6.1 channel Bass Manager. Dual 12" magnetically shielded long throw cone drivers to produce up to 118dB SPL in half space. 500 W amplifier with very low THD and IM distortion. Driver overload protection and power-on signal muting. SUM OUT to enable coupling two or more subwoofers for increased SPL.	2 686,00
7073 APM	Subwoofer. LF extension down to 19Hz. Flexible 6.1 channel Bass Manager. Four 12" magnetically shielded long throw cone drivers to produce up to 124dB SPL in half space. 1000 W amplifier with very low THD and IM distortion. Driver and amplifier overload protection and power-on signal muting. SUM OUT to enable coupling of two or more subwoofers for increased SPL for larger systems.	4 812,68

### Active DSP Subwoofer Systems

7260 AP	DSP Active Subwoofer featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Single 210 mm (10") magnetically shielded long throw cone driver with 120 W amplifier to produce up to 108 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration.	1 706,40
7261 APM	SE7261A DSP Active Subwoofer featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Single 210 mm (10") magnetically shielded long throw cone driver with 120 W amplifier to produce up to 108 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM.SE™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration. GLM.SE™ software with SE7261A subwoofer can control up to 8 pcs. of 8130 A loudspeakers.	1 706,40
7270 AP	Active Subwoofer featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Single 300 mm (12") magnetically shielded long throw cone driver with 250 W amplifier to produce up to 112 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration.	2 257,82

SYMBOL	OPIS PRODUKTU W ORYGINALE	CENA w EUR netto
7271 AP	Active Subwoofer featuring the Genelec Lamina Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Dual 300 mm (12") magnetically shielded long throw cone driver with 500 W amplifier to produce up to 118 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration.	3 076,26

### GLM Packages & Accessories

8200-601	GLM 1.2.0 Genelec Loudspeaker Manager Package GLM™ Genelec Loudspeaker Manager package featuring AutoCal™ includes: software CD (PC & Mac), GLM System Operating Manual, Quick Connection Guide, GLM™ Network Interface with built-in microphone amplifier and soundcard, USB cable, Network cable, Genelec 8200A Calibration microphone and holder, 3.5mm jack-jack Measurement Signal cable and cable labels. GLM™ software is available for Windows XP and Mac OS X, both Power PC and Intel based platforms operating systems.	494,54
8200-602	GLM 1.2.0 Multiroom Expansion package GLM™ Multiroom Expansion package includes: GLM™ Network Interface with built-in microphone amplifier and soundcard, USB cable, Network cable and Cable labels. This package is useful for multiroom facilities as it saves purchasing multiple microphones and other parts. (No microphone or Software included)	199,08
8200-501	GLM.SE Genelec Loudspeaker Manager Package GLM.SE™ Genelec Loudspeaker Manager package for SE7261A featuring AutoCal™ includes: software CD. GLM.SE System Operating Manual, Quick Connection Guide, GLM™ Network Interface with built-in microphone amplifier, USB cable, Network cable, Genelec 8200A Calibration microphone and holder, 3.5 mm jack-jack Measurement Signal cable and cable labels. GLM.SE™ software is available for Windows XP (later for Mac).	396,58
8200-502	GLM Multiroom Expansion package including GLM Network Interface with built-in microphone amplifier, USB cable, Network cable and Cable labels. This package is useful for multiroom facilities as it saves purchasing multiple microphones and other parts.	199,08
AD9200A	AD9200A A/D Converter 8-channel A to D converter providing analogue inputs into 4 AES/EBU outputs for the 7200-series DSP subwoofers. 1U high, 19", including one 8ch balanced analogue inputs on DB 25 pin connector with M2,5 metric threads (Tascam standard) 192 kHz / 24Bit internal sample rate converter. Separate 12 volt power supply is included.	545,10
8000-910	Griffin Volume Control. PowerMate aluminium, USB volume control, software for PC and Mac included.	90,06

### Active Signal Balancer

DI8A	DI8A 8-Channel Active Balancer to convert an unbalanced line signal (RCA) to a balanced line signal (XLR). +6dB switch to raise signal level. One channel with duplicated outputs.	595,66
------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------

### Options for Two-Way Bi-Amplified Active Monitors

Options for 6010 A		
6010-410B	Wall mount bracket, black (included in 6010 A)	9,48
6010-410W	Wall mount bracket, white (included in 6010 A)	9,48
8010-408	Stand plate for 6010 A Iso-Pod (K&M 19621.329.55)	33,18
8010-408W	Stand plate, white for 6010A Iso-Pod (K&M 19621.329.57)	33,18
8010-205	Table stand with Glass base (K&M 23280.300.00)	79,00

SYMBOL	OPIS PRODUKTU W ORYGINALE	CENA w EUR netto
8010-202B	Wall & Ceiling mount, black	25,28
8010-202S	Wall & Ceiling mount, silver	25,28
8010-202W	Wall & Ceiling mount, white	25,28
6010-421	Soft carrying bag for two monitors	56,88

Options for 8020 A (fits also for 6010 A if needed)		
8000-409B	Floor stand (K&M 26741.029.55)	110,60
8000-403	Floor stand (K&M 26000.329.55)	53,72
8000-412B	Wall mount with T-plate, black (K&M 24179.000.55)	45,82
8000-412W	Wall mount with T-plate, black (K&M 24179.000.57)	45,82
8000-402B	Wall mounting bracket, black (K&M 24475.000.55)	91,64
8000-402W	Wall mounting bracket, white (K&M 24475.000.57)	91,64
8000-410B	Wall mount bracket, black (included in 8020A)	4,74
8000-410W	Wall mount bracket, white (included in 8020A)	4,74
8000-406	Table stand (K&M 23310.370.55)	48,98
8020-408	Stand plate for 8020 Iso-Pod (K&M 19622.329.55)	34,76
8000-415B	Ceiling mount, black (K&M 24490.000.55)	268,60
8000-417B	Clamp and Truss mount, black (K&M 24495.000.55)	170,64
8000-432	Security wire with hook for truss	18,96
8000-419B	36mm tube adapter with 3/8" thread, black (K&M 24521.300.55)	55,30
8000-418B	Security Wire (K&M 24521.901.55)	23,70
8000-425B	Fixed telescopic table stand (K&M 23360.300.55)	47,40
8000-430	Carrying strap for one monitor	9,48
8000-435B	Ceiling mount short, black (K&M 24485.000.55)	91,64
8000-435W	Ceiling mount short, white (K&M 24485.000.57)	91,64
8000-440B	Cluster mount for 3 speakers, black	176,96
8000-440W	Cluster mount for 3 speakers, white	176,96
8020-490	Half 19" Rack mount kit for one 8020 (two units needed for full 19")	67,94
8020-421	Soft carrying bag for two monitors	56,88
8000-902B	Slotwall bracket for 8020A and 8030A standplate (K&M 44102.029.55)	31,60

Options for 8030 A and 8130 A		
8000-409B	Floor stand (K&M 26741.029.55)	110,60
8000-412B	Wall mount with T-plate, black (K&M 24179.000.55)	45,82
8000-412W	Wall mount with T-plate, black (K&M 24179.000.57)	45,82
8000-402B	Wall mounting bracket, black (K&M 24475.000.55)	91,64
8000-402W	Wall mounting bracket, white (K&M 24475.000.57)	91,64
8000-410B	Wall mount bracket, black (included in 8020A)	4,74
8000-410W	Wall mount bracket, white (included in 8020A)	4,74
8000-406	Table stand (K&M 23310.370.55)	48,98
8030-408	Stand plate for 8030/8130 Iso-Pod (K&M 19623.329.55)	39,50
8000-415B	Ceiling mount, black (K&M 24490.000.55)	268,60
8000-417B	Clamp and Truss mount, black (K&M 24495.000.55)	170,64
8000-432	Security wire with hook for truss	18,96
8000-419B	36mm tube adapter with 3/8" thread, black (K&M 24521.300.55)	55,30
8000-418B	Security Wire (K&M 24521.901.55)	23,70
8000-425B	Fixed telescopic table stand (K&M 23360.300.55)	47,40
8000-430	Carrying strap for one monitor	9,48
8000-435B	Ceiling mount short, black (K&M 24485.000.55)	91,64
8000-435W	Ceiling mount short, white (K&M 24485.000.57)	91,64
8000-440B	Cluster mount for 3 speakers, black	176,96
8000-440W	Cluster mount for 3 speakers, white	176,96

SYMBOL	OPIS PRODUKTU W ORYGINALE	CENA w EUR netto
8030-421	Soft carrying bag for two monitors	58,46
8000-902B	Slotwall bracket for 8020A and 8030A standplate (K&M 44102.029.55)	31,60

Options for 8040 A and 8240 A		
8000-400	Floor stand "Genelec design", 1100/1700mm high (K&M 26785.000.56)	268,60
8000-409B	Floor stand (K&M 26741.029.55)	110,60
8000-401B	Wall mount, black (K&M 24180.000.55)	34,76
8000-401W	Wall mount, white (K&M 24180.000.57)	34,76
8000-402B	Wall mounting bracket, black (K&M 24475.000.55)	91,64
8000-402W	Wall mounting bracket, white (K&M 24475.000.57)	91,64
8000-406	Table stand (K&M 23310.370.55)	48,98
8040-408	Stand plate for 8040 Iso-Pod (K&M 19624.329.55)	44,24
8000-415B	Ceiling mount, black (K&M 24490.000.55)	268,60
8000-417B	Clamp and Truss mount, black (K&M 24495.000.55)	170,64
8000-432	Security wire with hook for truss	18,96
8000-419B	36mm tube adapter with 3/8" thread, black (K&M 24521.300.55)	55,30
8000-418B	Security Wire (K&M 24521.901.55)	23,70
8000-430	Carrying strap for one monitor	9,48
8000-435B	Ceiling mount short, black (K&M 24485.000.55)	91,64
8000-435W	Ceiling mount short, white (K&M 24485.000.57)	91,64
8040-421	Soft carrying bag for two monitors	71,10
8040-450B	Flush mount kit	257,54
8000-904B	Slotwall bracket for 8040A and 8050A standplate (K&M 44104.029.55)	33,18

Options for 8050 A and 8250 A		
8000-400	Floor stand "Genelec design", 1100/1700mm high (K&M 26785.000.56)	268,60
8000-409B	Floor stand (K&M 26741.029.55)	110,60
8000-402B	Wall mounting bracket, black (K&M 24475.000.55)	91,64
8000-402W	Wall mounting bracket, white (K&M 24475.000.57)	91,64
8050-408	Stand plate for 8050 Iso-Pod (K&M 19625.329.55)	48,98
8000-415B	Ceiling mount, black (K&M 24490.000.55)	268,60
8000-417B	Clamp and Truss mount, black (K&M 24495.000.55)	170,64
8000-432	Security wire with hook for truss	18,96
8000-419B	36mm tube adapter with 3/8" thread, black (K&M 24521.300.55)	55,30
8000-418B	Security Wire (K&M 24521.901.55)	23,70
8000-430	Carrying strap for one monitor	9,48
8000-435B	Ceiling mount short, black (K&M 24485.000.55)	91,64
8000-435W	Ceiling mount short, white (K&M 24485.000.57)	91,64
8050-421	Soft carrying bag for one monitor	64,78
8050-450B	Flush mount kit	282,82
8000-904B	Slotwall bracket for 8040A and 8050A standplate (K&M 44104.029.55)	33,18

Options for 1032 A		
1032-450B	Stand plate with 3/8" thread, tiltable 15° black (K&M 24455.000.55) , needs a stand, 8000-409B	102,70
8000-409B	Floor stand with 3/8" thread in top. (K&M 26741.029.55)	110,60
1032-460B	Wall mount black, tiltable 15° (K&M 24453.000.55)	221,20
1032-403	Magnetic shield upgrade kit	48,98
1032-409	Grille, black	66,36
1037-412	Rack Mount Adapter for amplifier unit (without cables)	206,98
1039-203	Cable, 2 m	115,34
1039-204	Cable, 5 m	156,42



SYMBOL	OPIS PRODUKTU W ORYGINALE	CENA w EUR netto
1039-205	Cable, 10 m	230,68
1039-206	Cable, 15 m	301,78
1039-207	Cable, 20 m	376,04

## Options for Three-Way Tri-Amplified Active Monitors

### Options for 1037 C

1001-406	Handles (set of two, factory installed)	151,68
1037-414B	Wall mount (K&M 24457.000.55)	431,34
1037-415B	Floor stand (K&M 45100.000.55)	925,88
1037-409	Grille, black	118,50
1037-412	Rack Mount Adapter for amplifier unit (without cables)	206,98
1039-203	Cable, 2 m	115,34
1039-204	Cable, 5 m	156,42
1039-205	Cable, 10 m	230,68
1039-206	Cable, 15 m	301,78
1039-207	Cable, 20 m	376,04

### Options for 1038 B and 1038 BC

1001-406	Handles for 1038 A/B (set of two, factory installed)	151,68
1038-415B	Floor stand (not for BC) (K&M 45110.000.55)	925,88
1038-409	Grille for 1038 A/B, black	129,56
1038-409 BC	Grille for 1038 BC, black	129,56
1038-421	Rack Mount Adapter for 1038 A/B amp without cables	287,56
1039-203	Cable, 2 m	115,34
1039-204	Cable, 5 m	156,42
1039-205	Cable, 10 m	230,68
1039-206	Cable, 15 m	301,78
1039-207	Cable, 20 m	376,04

## Options for Main Control Room Active Monitors

### Options for 1034 B and 1034 BCM

1034-403 B	Magnetic shielding for 1034B (1034BCM is always shielded)	229,10
1034-409 B	Grille for 1034 B, black	88,48
1034-409 BC	Grille for 1034 BC, black	88,48
1039-203	Cable, 2 m	115,34
1039-204	Cable, 5 m	156,42
1039-205	Cable, 10 m	230,68
1039-206	Cable, 15 m	301,78
1039-207	Cable, 20 m	376,04

### Options for 1039 A

1039-403	Magnetic shielding	229,10
1039-409	Grille, black	90,06
1039-203	Cable, 2 m	115,34
1039-204	Cable, 5 m	156,42
1039-205	Cable, 10 m	230,68
1039-206	Cable, 15 m	301,78
1039-207	Cable, 20 m	376,04



SYMBOL	OPIS PRODUKTU W ORYGINALE	CENA w EUR netto
--------	---------------------------	------------------

Options for 1035 B		
1035-409	Grille, black	99,54
1035-204	Cable, 5 m	440,82
1035-205	Cable, 10 m	515,08
1035-206	Cable, 15 m	601,98
1035-207	Cable, 20 m	1 466,24
1035-208	Cable, 25 m	1 779,08
1035-209	Cable, 30 m	2 102,98

Options for 1036 A		
1036-409	Grille, black	99,54
1035-204	Cable, 5 m	440,82
1035-205	Cable, 10 m	515,08
1035-206	Cable, 15 m	601,98
1035-207	Cable, 20 m	1 466,24
1035-208	Cable, 25 m	1 779,08
1035-209	Cable, 30 m	2 102,98

### Options for Active Monitoring Subwoofer Systems

Options for 7060 B, 7070 A, 7071 A and 7260 A, 7270 A, 7271 A and 7073 A		
1092-400	Remote bypass switch box with 1/4" jack	72,68
7000-415	Remote Power/Overload LED box with 5m cable, RJ11 connector	91,64
7000-416	Remote control box for bypass and +10 dB LFE functions with 5m cable, RJ11 connector	104,28

Cable		
1510-302B	Hybrid cable, black (Power and AES/EBU), 50m reels	323,90
1550-105	Loom 5m, with DB 25 pin male and 8 pcs. XLR female connectors, providing AD9200A connectivity to 8 pcs. XLR balanced monitor outputs.	281,24