

| SYMBOL   | OPIS PRODUKTU W ORYGINALE  | CENA w EUR brutto |
|--|--|-------------------|
| <b>Analog Two-Way Bi-Amplified Active Monitors</b> |  |                   |
| 6010 APM   | Compact, Two-Way Active Loudspeaker. Solid die-cast aluminium MDE™ cabinet (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 76 mm (3") LF and 19 mm (.75") HF drive units. RCA input corrector. Integrated crossover and amps -12W and 12W. Room response controls on rear panel. On-Off and volume control on the back panel. 3/8" mic stand thread. Integrated M6 mounting threads and VESA 75mm M4 in the back. Wall mount bracket included. Iso-Pod™ table support included. Matt black painted finish.   | 178,54            |
| 6010 ASM   | As 6010 APM above but in silver painted finish   | 178,54            |
| 6010 AWM   | As 6010 APM above but in white painted finish  | 178,54            |
| 6010 AZM   | As 6010 APM above but in hand polished aluminium finish  | 267,02            |
| 8020 APM   | Compact, Two-Way Active Nearfield Monitor. Solid die-cast aluminium MDE™ cabinet (Minimum Diffraction Enclosure) cabinet including DCW™ protection grills and magnetically shielded, 100 mm (4") LF and 19 mm (.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 20W and 20W. Room response controls on rear panel. On-Off and volume control in one on the front. 3/8" mic stand thread. Integrated M6 mounting threads in the back. Wall mount bracket included. Iso-Pod™ table support included. Matt black painted finish.   | 273,34            |
| 8020 ASM   | As 8020 APM above but in silver painted finish   | 293,88            |
| 8020 AWM   | As 8020 APM above but in white painted finish  | 293,88            |
| 8020 AZM   | As 8020 APM above but in hand polished aluminium finish  | 674,66            |
| 8030 APM   | Compact, two way Active Nearfield Monitor. Solid die-cast aluminium MDE cabinet (Minimum Diffraction Enclosure) including DCW protection grills and magnetically shielded, 130mm (5") LF and 19mm (0.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 40 W and 40 W. Room response controls on rear panel. On-Off and volume control on the front. 3/8" mic stand thread. Integrated Omnimount 20.5WA or CA mounting threads in the back. Iso-Pod table support included. Matt black painted finish.   | 413,96            |
| 8030 ASM   | As 8030 APM above but in silver painted finish   | 431,34            |
| 8030 AWM   | As 8030 APM above but in white painted finish  | 431,34            |
| 8030 AZM   | As 8030 APM above but in hand polished aluminium finish  | 936,94            |
| 8130 AP  | Compact, Two-Way Digital Input Active Monitor. As 8030APM but with AES/EBU Digital input combined with analogue input XLR connector. Solid die-cast aluminium MDE cabinet (Minimum Diffraction Enclosure) including DCW protection grills and magnetically shielded, 130mm (5") LF and 19mm (0.75") HF drive units. Balanced XLR input/output connectors. Integrated crossover and amps - 40 W and 40 W. Room response controls on rear panel. On-Off and volume control on the front. 3/8" mic stand thread. Integrated Omnimount 20.5WA or CA mounting threads in the back. Iso-Pod table support included. Matt black painted finish. | 597,24            |
| 8040 APM   | Two way Active Nearfield Monitor. Solid die-cast aluminium MDE cabinet (Minimum Diffraction Enclosure) including DCW protection grills and magnetically shielded, 165mm (6.5") LF and 19mm (0.75") HF drive units. Balanced XLR connector. Integrated crossover and amps - 90 W and 90 W. Integrated Omnimount 20.5WA or CA and K&M 24180 mounting threads in the back. M10 stand thread in bottom. Room response controls on rear panel. Iso-Pod table support included. Matt black painted finish.   | 663,60            |
| 8040 AWM   | As 8040 APM above but in white painted finish  | 695,20            |
| 8040 AZM   | As 8040 APM above but in hand polished aluminium finish  | 1 341,42          |

| SYMBOL   | OPIS PRODUKTU W ORYGINALE   | CENA w EUR brutto |
|----------|---|-------------------|
| 8050 APM | Two way Active Nearfield Monitor. Solid die-cast aluminium MDE cabinet (Minimum Diffraction Enclosure) including DCW protection grills and magnetically shielded, 205mm (8") LF and 25mm (1") HF drive units. Balanced XLR connector. Integrated crossover and amps - 150 W and 120 W. Integrated Omnimount 20.5WA or CA mounting threads in the back. M10 stand thread in bottom. Room response controls on rear panel. Iso-Pod table support included. Matt black painted finish. | 1 079,14          |
| 8050 AWM | As 8050 APM above but in white painted finish   | 1 134,44          |
| 8050 AZM | As 8050 APM above but in hand polished aluminium finish   | 2 129,84          |

### DSP Two-Way Bi-Amplified Active Monitors

|          |  |          |
|----------|--|----------|
| 8240 APM | DSP Bi-amplified Monitor System. Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ and magnetically shielded 165 mm (6.5") LF and 19 mm (3/4") HF drive units. Integrated crossover and amplifiers – 90 W and 90 W. Balanced analog XLR input connector and digital AES/EBU In and Thru XLR connectors. Dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Controls for Stand-Alone operational mode on rear panels. Integrated rear M6 mounting threads. Iso-Pod™ table support included. Matt black painted finish. | 954,32   |
| 8250 APM | DSP Bi-amplified Monitor System. Solid die-cast aluminium MDE™ (Minimum Diffraction Enclosure) cabinet including DCW™ and magnetically shielded 205 mm (8") LF and 25 mm (1") HF drive units. Integrated crossover and amplifiers – 150 W and 120 W. Balanced analog XLR input connector and digital AES/EBU In and Thru XLR connectors. Dual Genelec Loudspeaker Manager™ (GLM™). Control Network connectors. Controls for Stand-Alone operational mode on rear panels. Integrated rear M6 mounting threads. Iso-Pod™ table support included. Matt black painted finish.  | 1 385,66 |

### Two-Way Bi-Amplified Active Monitors

|          |  |          |
|----------|--|----------|
| 1032 APM | Two way Active Near Field Monitor, Magnetically shielded 250mm (10") LF 25mm (1") HF drive units. Integrated crossover and amps, 180W and 120W. EQ controls on rear panel. Durable black painted "Producer" finish. THX ® pm3 certified. | 1 414,10 |
| 1032 AM  | As 1032APM but with black veneer finish. THX ® pm3 certified.  | 1 414,10 |

### Three-Way Tri-Amplified Active Monitors

|          |   |          |
|----------|---|----------|
| 1037 CEM | Three-way Active Mid Field Monitor, Magnetically shielded 300mm (12") LF, GENELEC 130mm (5") MF and 25mm (1") HF drive units. Integrated crossovers and amps, 180W, 120W and 120W. Tone controls on rear panel. Black veneer finish. THX ® pm3 certified. | 2 877,18 |
| 1037 CPM | As 1037B but with durable black painted "Producer" finish. THX ® pm3 certified.   | 2 883,50 |
| 1038 BEM | Three-way Active Mid Field Monitor, 15" LF, GENELEC 130mm (5") MF and 25mm (1") HF drive units. Integrated crossovers and amps, 400W, 120W, and 120W. Tone controls on rear panel. Black veneer finish. THX ® pm3 certified.                              | 4 136,44 |
| 1038 BPM | As 1038BEM but with durable black painted "Producer" finish. THX ® pm3 certified.   | 4 144,34 |

| SYMBOL       | OPIS PRODUKTU W ORYGINALE   | CENA w EUR brutto |
|--------------|---|-------------------|
| 1038 BCPM-VL | Center channel three-way Active Mid Field Monitor, Magnetically shielded Dual 10" LF, GENELEC 130mm (5") MF, 25mm (1") HF drive units. System includes speaker enclosure in durable black painted "Producer" finish, a single 19" electronics with crossovers, tone controls and amplifier modules. THX ® pm3 certified. Amplification: 400W, 120W, 120W. 10m cable included. | 4 657,84          |
| 1038 BCPM-VR |   | 4 657,84          |
| 1038 BCPM-HU |   | 4 657,84          |
| 1038 BCPM-HD |   | 4 657,84          |

## Main Control Room Active Monitors

|            |  |          |
|------------|--|----------|
| 1034 BM-VU | Three-way Main Control Room Active Monitor. Soffit mount design. Magnetically shielded, dual 12" LF, GENELEC 5" MF, and 25 mm (1") HFdrive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with cross-overs, room response controls and amplifier modules. Amplification 2 x 400W, 350W, and 120W per amp module. 10 m cable included as standard. | 7 414,94 |
| 1034 BM-VD |  | 7 414,94 |
| 1034 BM-HL |  | 7 414,94 |
| 1034 BM-HR |  | 7 414,94 |

|             |  |          |
|-------------|--|----------|
| 1034 BCM-VL | Center channel three- way Active Monitor System for soffit. Magnetically shielded Dual 300mm (12") LF, GENELEC 130mm (5") MF, 25mm (1") HF drive units. Amplification 400W, 350W, 120W. EQ controls on remote amp panel. System includes 1 speaker enclosure in black painted veneer finish, a single 19" remote electronics unit and 10m cables. Matches the 1034B Main Control Room Monitor Systems. | 7 966,36 |
| 1034 BCM-VR |  | 7 966,36 |
| 1034 BCM-HU |  | 7 966,36 |
| 1034 BCM-HD |  | 7 966,36 |

|            |  |          |
|------------|--|----------|
| 1039 AM-VU | Three-way Main Control Room Active Monitor. Soffit mount design. Magnetically shielded, dual 385 mm (15") LF, GENELEC 130 mm (5") MF, and 25 mm (1") HF drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 2 x 400W, 350W, & 120W per amp module. 10 m cable included as standard. | 8 451,42 |
| 1039 AM-VD |  | 8 451,42 |
| 1039 AM-HL |  | 8 451,42 |
| 1039 AM-HR |  | 8 451,42 |

|           |   |           |
|-----------|---|-----------|
| 1035 B-VU | Three-way Main Control Room Active Monitor System for large control rooms, soffit mount design. Dual 385mm (15") LF, Dual GENELEC 130mm (5") MF and 25mm (1") HF compression drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 2 x 1100W, 300W (3.1kW) per channel. 10 m cable included as standard. | 22 582,94 |
| 1035 B-VD |   | 22 582,94 |
| 1035 B-HL |   | 22 582,94 |
| 1035 B-HR |   | 22 582,94 |

|           |   |           |
|-----------|---|-----------|
| 1036 A-VU | Three-way Main Control Room Active Monitor System for large control rooms, soffit mount design. Dual 460mm (18") LF, Dual GENELEC 130mm (5") MF and 25mm (1") HF compression drive units. System includes speaker enclosure in black painted veneer finish, a single 19" electronics with crossovers, room response controls and amplifier modules. Amplification 2 x 1100W, 600 W and 300W (3.1kW) per channel. 10 m cable included as standard. | 24 148,72 |
| 1036 A-VD |   | 24 148,72 |
| 1036 A-HL |   | 24 148,72 |
| 1036 A-HR |   | 24 148,72 |

## Active Analog Subwoofer Systems

|          |   |        |
|----------|---|--------|
| 5040 APM | Active Subwoofer. Deep drawn steel cabinet with optimized reflex port, design to support up to 5 pcs. of 6010 A. System volum included. Single 165mm (6,5") magnetically shielded long throw cone driver to produce up to 98 dB SPL in half space. RCA in and output connectors. 40W amplifier with very low THD and IM distortion. | 355,50 |
| 5040 ASM | As 5040 APM above but in silver painted finish  | 355,50 |
| 5040 AWM | As 5040 APM above but in white painted finish   | 355,50 |
| 7050 BP  | Active Subwoofer featuring the new Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and 5.1 channel Bass Management system. Single 8" magnetically shielded long throw cone driver to produce up to 100 dB SPL in half space. 70 W amplifier with very low THD and IM distortion.                                       | 669,92 |

| SYMBOL   | OPIS PRODUKTU W ORYGINALE   | CENA w EUR brutto |
|----------|---|-------------------|
| 7060 BP  | Active Subwoofer featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 6.1 channel Bass Manager. Single 210 mm (10") magnetically shielded long throw cone driver to produce up to 108 dB SPL in half space. 120 W amplifier with very low THD and IM distortion. Driver overload protection and power-on signal muting. Sum out to enable coupling of two or more subwoofers for increased SPL. | 1 294,02          |
| 7070 APM | Active Subwoofer featuring the new Genelec Laminar Spiral Enclosure (LSE) bass reflex cabinet and highly configurable 6.1 channel Bass Manager. Single 12" magnetically shielded long throw cone driver to produce up to 112 dB SPL in half space. 250 W amplifier with very low THD and IM distortion. Driver overload protection and power-on signal muting. SUM OUT to enable coupling two or more subwoofers for increased SPL.           | 1 782,24          |
| 7071 APM | Active Subwoofer featuring the new Genelec Laminar Spiral Enclosure (LSE) bass reflex cabinet and highly configurable 6.1 channel Bass Manager. Dual 12" magnetically shielded long throw cone drivers to produce up to 118dB SPL in half space. 500 W amplifier with very low THD and IM distortion. Driver overload protection and power-on signal muting. SUM OUT to enable coupling two or more subwoofers for increased SPL.             | 2 686,00          |
| 7073 APM | Subwoofer. LF extension down to 19Hz. Flexible 6.1 channel Bass Manager. Four 12" magnetically shielded long throw cone drivers to produce up to 124dB SPL in half space. 1000 W amplifier with very low THD and IM distortion. Driver and amplifier overload protection and power-on signal muting. SUM OUT to enable coupling of two or more subwoofers for increased SPL for larger systems.   | 4 812,68          |

## Active DSP Subwoofer Systems

|          |   |          |
|----------|---|----------|
| 7260 AP  | DSP Active Subwoofer featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Single 210 mm (10") magnetically shielded long throw cone driver with 120 W amplifier to produce up to 108 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration.   | 1 706,40 |
| 7261 APM | SE7261A DSP Active Subwoofer featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Single 210 mm (10") magnetically shielded long throw cone driver with 120 W amplifier to produce up to 108 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM.SE™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration. GLM.SE™ software with SE7261A subwoofer can control up to 8 pcs. of 8130 A loudspeakers. | 1 706,40 |
| 7270 AP  | Active Subwoofer featuring the Genelec Laminar Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Single 300 mm (12") magnetically shielded long throw cone driver with 250 W amplifier to produce up to 112 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration.   | 2 257,82 |

| SYMBOL  | OPIS PRODUKTU W ORYGINALE  | CENA w EUR brutto |
|---------|--|-------------------|
| 7271 AP | Active Subwoofer featuring the Genelec Lamina Spiral Enclosure™ (LSE™) bass reflex cabinet and highly configurable 8 channels digital Bass Management System. Dual 300 mm (12") magnetically shielded long throw cone driver with 500 W amplifier to produce up to 118 dB SPL in half space. AES/EBU In/Out XLR connectors and dual Genelec Loudspeaker Manager™ (GLM™) Control Network connectors. Connector panel controls for Stand-Alone operational mode including Room Response and LFE channel configuration. | 3 076,26          |

## GLM Packages & Accessories

|          |   |        |
|----------|---|--------|
| 8200-601 | GLM 1.2.0 Genelec Loudspeaker Manager Package<br>GLM™ Genelec Loudspeaker Manager package featuring AutoCal™ includes: software CD (PC & Mac), GLM System Operating Manual, Quick Connection Guide, GLM™ Network Interface with built-in microphone amplifier and soundcard, USB cable, Network cable, Genelec 8200A Calibration microphone and holder, 3.5mm jack-jack Measurement Signal cable and cable labels. GLM™ software is available for Windows XP and Mac OS X, both Power PC and Intel based platforms operating systems. | 494,54 |
| 8200-602 | GLM 1.2.0 Multiroom Expansion package<br>GLM™ Multiroom Expansion package includes: GLM™ Network Interface with built-in microphone amplifier and soundcard, USB cable, Network cable and Cable labels. This package is useful for multiroom facilities as it saves purchasing multiple microphones and other parts. (No microphone or Software included)   | 199,08 |
| 8200-501 | GLM.SE Genelec Loudspeaker Manager Package<br>GLM.SE™ Genelec Loudspeaker Manager package for SE7261A featuring AutoCal™ includes: software CD. GLM.SE System Operating Manual, Quick Connection Guide, GLM™ Network Interface with built-in microphone amplifier, USB cable, Network cable, Genelec 8200A Calibration microphone and holder, 3.5 mm jack-jack Measurement Signal cable and cable labels. GLM.SE™ software is available for Windows XP (later for Mac).   | 396,58 |
| 8200-502 | GLM Multiroom Expansion package<br>including GLM Network Interface with built-in microphone amplifier, USB cable, Network cable and Cable labels. This package is useful for multiroom facilities as it saves purchasing multiple microphones and other parts.  | 199,08 |
| AD9200A  | AD9200A A/D Converter<br>8-channel A to D converter providing analogue inputs into 4 AES/EBU outputs for the 7200-series DSP subwoofers. 1U high, 19", including one 8ch balanced analogue inputs on DB 25 pin connector with M2,5 metric threads (Tascam standard) 192 kHz / 24Bit internal sample rate converter. Separate 12 volt power supply is included.  | 545,10 |
| 8000-910 | Griffin Volume Control. PowerMate aluminium, USB volume control, software for PC and Mac included.  | 90,06  |

## Active Signal Balancer

|      |  |        |
|------|--|--------|
| DI8A | DI8A 8-Channel Active Balancer to convert an unbalanced line signal (RCA) to a balanced line signal (XLR). +6dB switch to raise signal level. One channel with duplicated outputs. | 595,66 |
|------|--|--------|

## Options for Two-Way Bi-Amplified Active Monitors

| Options for 6010 A |   |       |
|--------------------|---|-------|
| 6010-410B          | Wall mount bracket, black (included in 6010 A)          | 9,48  |
| 6010-410W          | Wall mount bracket, white (included in 6010 A)          | 9,48  |
| 8010-408           | Stand plate for 6010 A Iso-Pod (K&M 19621.329.55)       | 33,18 |
| 8010-408W          | Stand plate, white for 6010A Iso-Pod (K&M 19621.329.57) | 33,18 |
| 8010-205           | Table stand with Glass base (K&M 23280.300.00)          | 79,00 |

| SYMBOL    | OPIS PRODUKTU W ORYGINALE          | CENA w EUR brutto |
|-----------|------------------------------------|-------------------|
| 8010-202B | Wall & Ceiling mount, black        | 25,28             |
| 8010-202S | Wall & Ceiling mount, silver       | 25,28             |
| 8010-202W | Wall & Ceiling mount, white        | 25,28             |
| 6010-421  | Soft carrying bag for two monitors | 56,88             |

| Options for 8020 A (fits also for 6010 A if needed) |  |        |
|---|--|--------|
| 8000-409B   | Floor stand (K&M 26741.029.55)                                       | 110,60 |
| 8000-403  | Floor stand (K&M 26000.329.55)                                       | 53,72  |
| 8000-412B   | Wall mount with T-plate, black (K&M 24179.000.55)                    | 45,82  |
| 8000-412W   | Wall mount with T-plate, black (K&M 24179.000.57)                    | 45,82  |
| 8000-402B   | Wall mounting bracket, black (K&M 24475.000.55)                      | 91,64  |
| 8000-402W   | Wall mounting bracket, white (K&M 24475.000.57)                      | 91,64  |
| 8000-410B   | Wall mount bracket, black (included in 8020A)                        | 4,74   |
| 8000-410W   | Wall mount bracket, white (included in 8020A)                        | 4,74   |
| 8000-406  | Table stand (K&M 23310.370.55)                                       | 48,98  |
| 8020-408  | Stand plate for 8020 Iso-Pod (K&M 19622.329.55)                      | 34,76  |
| 8000-415B   | Ceiling mount, black (K&M 24490.000.55)                              | 268,60 |
| 8000-417B   | Clamp and Truss mount, black (K&M 24495.000.55)                      | 170,64 |
| 8000-432  | Security wire with hook for truss                                    | 18,96  |
| 8000-419B   | 36mm tube adapter with 3/8" thread, black (K&M 24521.300.55)         | 55,30  |
| 8000-418B   | Security Wire (K&M 24521.901.55)                                     | 23,70  |
| 8000-425B   | Fixed telescopic table stand (K&M 23360.300.55)                      | 47,40  |
| 8000-430  | Carrying strap for one monitor                                       | 9,48   |
| 8000-435B   | Ceiling mount short, black (K&M 24485.000.55)                        | 91,64  |
| 8000-435W   | Ceiling mount short, white (K&M 24485.000.57)                        | 91,64  |
| 8000-440B   | Cluster mount for 3 speakers, black                                  | 176,96 |
| 8000-440W   | Cluster mount for 3 speakers, white                                  | 176,96 |
| 8020-490  | Half 19" Rack mount kit for one 8020 (two units needed for full 19") | 67,94  |
| 8020-421  | Soft carrying bag for two monitors                                   | 56,88  |
| 8000-902B   | Slotwall bracket for 8020A and 8030A standplate (K&M 44102.029.55)   | 31,60  |

| Options for 8030 A and 8130 A |  |        |
|-------------------------------|--|--------|
| 8000-409B                     | Floor stand (K&M 26741.029.55)                               | 110,60 |
| 8000-412B                     | Wall mount with T-plate, black (K&M 24179.000.55)            | 45,82  |
| 8000-412W                     | Wall mount with T-plate, black (K&M 24179.000.57)            | 45,82  |
| 8000-402B                     | Wall mounting bracket, black (K&M 24475.000.55)              | 91,64  |
| 8000-402W                     | Wall mounting bracket, white (K&M 24475.000.57)              | 91,64  |
| 8000-410B                     | Wall mount bracket, black (included in 8020A)                | 4,74   |
| 8000-410W                     | Wall mount bracket, white (included in 8020A)                | 4,74   |
| 8000-406                      | Table stand (K&M 23310.370.55)                               | 48,98  |
| 8030-408                      | Stand plate for 8030/8130 Iso-Pod (K&M 19623.329.55)         | 39,50  |
| 8000-415B                     | Ceiling mount, black (K&M 24490.000.55)                      | 268,60 |
| 8000-417B                     | Clamp and Truss mount, black (K&M 24495.000.55)              | 170,64 |
| 8000-432                      | Security wire with hook for truss                            | 18,96  |
| 8000-419B                     | 36mm tube adapter with 3/8" thread, black (K&M 24521.300.55) | 55,30  |
| 8000-418B                     | Security Wire (K&M 24521.901.55)                             | 23,70  |
| 8000-425B                     | Fixed telescopic table stand (K&M 23360.300.55)              | 47,40  |
| 8000-430                      | Carrying strap for one monitor                               | 9,48   |
| 8000-435B                     | Ceiling mount short, black (K&M 24485.000.55)                | 91,64  |
| 8000-435W                     | Ceiling mount short, white (K&M 24485.000.57)                | 91,64  |
| 8000-440B                     | Cluster mount for 3 speakers, black                          | 176,96 |
| 8000-440W                     | Cluster mount for 3 speakers, white                          | 176,96 |

| SYMBOL    | OPIS PRODUKTU W ORYGINALE  | CENA w EUR brutto |
|-----------|--|-------------------|
| 8030-421  | Soft carrying bag for two monitors                                 | 58,46             |
| 8000-902B | Slotwall bracket for 8020A and 8030A standplate (K&M 44102.029.55) | 31,60             |

| Options for 8040 A and 8240 A |  |        |
|-------------------------------|--|--------|
| 8000-400                      | Floor stand "Genelec design", 1100/1700mm high (K&M 26785.000.56)  | 268,60 |
| 8000-409B                     | Floor stand (K&M 26741.029.55)                                     | 110,60 |
| 8000-401B                     | Wall mount, black (K&M 24180.000.55)                               | 34,76  |
| 8000-401W                     | Wall mount, white (K&M 24180.000.57)                               | 34,76  |
| 8000-402B                     | Wall mounting bracket, black (K&M 24475.000.55)                    | 91,64  |
| 8000-402W                     | Wall mounting bracket, white (K&M 24475.000.57)                    | 91,64  |
| 8000-406                      | Table stand (K&M 23310.370.55)                                     | 48,98  |
| 8040-408                      | Stand plate for 8040 Iso-Pod (K&M 19624.329.55)                    | 44,24  |
| 8000-415B                     | Ceiling mount, black (K&M 24490.000.55)                            | 268,60 |
| 8000-417B                     | Clamp and Truss mount, black (K&M 24495.000.55)                    | 170,64 |
| 8000-432                      | Security wire with hook for truss                                  | 18,96  |
| 8000-419B                     | 36mm tube adapter with 3/8" thread, black (K&M 24521.300.55)       | 55,30  |
| 8000-418B                     | Security Wire (K&M 24521.901.55)                                   | 23,70  |
| 8000-430                      | Carrying strap for one monitor                                     | 9,48   |
| 8000-435B                     | Ceiling mount short, black (K&M 24485.000.55)                      | 91,64  |
| 8000-435W                     | Ceiling mount short, white (K&M 24485.000.57)                      | 91,64  |
| 8040-421                      | Soft carrying bag for two monitors                                 | 71,10  |
| 8040-450B                     | Flush mount kit  | 257,54 |
| 8000-904B                     | Slotwall bracket for 8040A and 8050A standplate (K&M 44104.029.55) | 33,18  |

| Options for 8050 A and 8250 A |  |        |
|-------------------------------|--|--------|
| 8000-400                      | Floor stand "Genelec design", 1100/1700mm high (K&M 26785.000.56)  | 268,60 |
| 8000-409B                     | Floor stand (K&M 26741.029.55)                                     | 110,60 |
| 8000-402B                     | Wall mounting bracket, black (K&M 24475.000.55)                    | 91,64  |
| 8000-402W                     | Wall mounting bracket, white (K&M 24475.000.57)                    | 91,64  |
| 8050-408                      | Stand plate for 8050 Iso-Pod (K&M 19625.329.55)                    | 48,98  |
| 8000-415B                     | Ceiling mount, black (K&M 24490.000.55)                            | 268,60 |
| 8000-417B                     | Clamp and Truss mount, black (K&M 24495.000.55)                    | 170,64 |
| 8000-432                      | Security wire with hook for truss                                  | 18,96  |
| 8000-419B                     | 36mm tube adapter with 3/8" thread, black (K&M 24521.300.55)       | 55,30  |
| 8000-418B                     | Security Wire (K&M 24521.901.55)                                   | 23,70  |
| 8000-430                      | Carrying strap for one monitor                                     | 9,48   |
| 8000-435B                     | Ceiling mount short, black (K&M 24485.000.55)                      | 91,64  |
| 8000-435W                     | Ceiling mount short, white (K&M 24485.000.57)                      | 91,64  |
| 8050-421                      | Soft carrying bag for one monitor                                  | 64,78  |
| 8050-450B                     | Flush mount kit  | 282,82 |
| 8000-904B                     | Slotwall bracket for 8040A and 8050A standplate (K&M 44104.029.55) | 33,18  |

| Options for 1032 A |  |        |
|--------------------|--|--------|
| 1032-450B          | Stand plate with 3/8" thread, tiltable 15° black (K&M 24455.000.55) , needs a stand, 8000-409B | 102,70 |
| 8000-409B          | Floor stand with 3/8" thread in top. (K&M 26741.029.55)  | 110,60 |
| 1032-460B          | Wall mount black, tiltable 15° (K&M 24453.000.55)  | 221,20 |
| 1032-403           | Magnetic shield upgrade kit  | 48,98  |
| 1032-409           | Grille, black  | 66,36  |
| 1037-412           | Rack Mount Adapter for amplifier unit (without cables)   | 206,98 |
| 1039-203           | Cable, 2 m   | 115,34 |
| 1039-204           | Cable, 5 m   | 156,42 |

| SYMBOL   | OPIS PRODUKTU W ORYGINALE | CENA w EUR brutto |
|----------|---------------------------|-------------------|
| 1039-205 | Cable, 10 m               | 230,68            |
| 1039-206 | Cable, 15 m               | 301,78            |
| 1039-207 | Cable, 20 m               | 376,04            |

### Options for Three-Way Tri-Amplified Active Monitors

#### Options for 1037 C

|           |  |        |
|-----------|--|--------|
| 1001-406  | Handles (set of two, factory installed)                | 151,68 |
| 1037-414B | Wall mount (K&M 24457.000.55)                          | 431,34 |
| 1037-415B | Floor stand (K&M 45100.000.55)                         | 925,88 |
| 1037-409  | Grille, black  | 118,50 |
| 1037-412  | Rack Mount Adapter for amplifier unit (without cables) | 206,98 |
| 1039-203  | Cable, 2 m   | 115,34 |
| 1039-204  | Cable, 5 m   | 156,42 |
| 1039-205  | Cable, 10 m  | 230,68 |
| 1039-206  | Cable, 15 m  | 301,78 |
| 1039-207  | Cable, 20 m  | 376,04 |

#### Options for 1038 B and 1038 BC

|             |  |        |
|-------------|--|--------|
| 1001-406    | Handles for 1038 A/B (set of two, factory installed) | 151,68 |
| 1038-415B   | Floor stand (not for BC) (K&M 45110.000.55)          | 925,88 |
| 1038-409    | Grille for 1038 A/B, black                           | 129,56 |
| 1038-409 BC | Grille for 1038 BC, black                            | 129,56 |
| 1038-421    | Rack Mount Adapter for 1038 A/B amp without cables   | 287,56 |
| 1039-203    | Cable, 2 m   | 115,34 |
| 1039-204    | Cable, 5 m   | 156,42 |
| 1039-205    | Cable, 10 m  | 230,68 |
| 1039-206    | Cable, 15 m  | 301,78 |
| 1039-207    | Cable, 20 m  | 376,04 |

### Options for Main Control Room Active Monitors

#### Options for 1034 B and 1034 BCM

|             |   |        |
|-------------|---|--------|
| 1034-403 B  | Magnetic shielding for 1034B (1034BCM is always shielded) | 229,10 |
| 1034-409 B  | Grille for 1034 B, black                                  | 88,48  |
| 1034-409 BC | Grille for 1034 BC, black                                 | 88,48  |
| 1039-203    | Cable, 2 m  | 115,34 |
| 1039-204    | Cable, 5 m  | 156,42 |
| 1039-205    | Cable, 10 m   | 230,68 |
| 1039-206    | Cable, 15 m   | 301,78 |
| 1039-207    | Cable, 20 m   | 376,04 |

#### Options for 1039 A

|          |                    |        |
|----------|--------------------|--------|
| 1039-403 | Magnetic shielding | 229,10 |
| 1039-409 | Grille, black      | 90,06  |
| 1039-203 | Cable, 2 m         | 115,34 |
| 1039-204 | Cable, 5 m         | 156,42 |
| 1039-205 | Cable, 10 m        | 230,68 |
| 1039-206 | Cable, 15 m        | 301,78 |
| 1039-207 | Cable, 20 m        | 376,04 |

| SYMBOL | OPIS PRODUKTU W ORYGINALE | CENA w EUR brutto |
|--------|---------------------------|-------------------|
|--------|---------------------------|-------------------|

| Options for 1035 B |               |          |
|--------------------|---------------|----------|
| 1035-409           | Grille, black | 99,54    |
| 1035-204           | Cable, 5 m    | 440,82   |
| 1035-205           | Cable, 10 m   | 515,08   |
| 1035-206           | Cable, 15 m   | 601,98   |
| 1035-207           | Cable, 20 m   | 1 466,24 |
| 1035-208           | Cable, 25 m   | 1 779,08 |
| 1035-209           | Cable, 30 m   | 2 102,98 |

| Options for 1036 A |               |          |
|--------------------|---------------|----------|
| 1036-409           | Grille, black | 99,54    |
| 1035-204           | Cable, 5 m    | 440,82   |
| 1035-205           | Cable, 10 m   | 515,08   |
| 1035-206           | Cable, 15 m   | 601,98   |
| 1035-207           | Cable, 20 m   | 1 466,24 |
| 1035-208           | Cable, 25 m   | 1 779,08 |
| 1035-209           | Cable, 30 m   | 2 102,98 |

### Options for Active Monitoring Subwoofer Systems

| Options for 7060 B, 7070 A, 7071 A and 7260 A, 7270 A, 7271 A and 7073 A |  |        |
|--|--|--------|
| 1092-400   | Remote bypass switch box with 1/4" jack  | 72,68  |
| 7000-415   | Remote Power/Overload LED box with 5m cable, RJ11 connector                          | 91,64  |
| 7000-416   | Remote control box for bypass and +10 dB LFE functions with 5m cable, RJ11 connector | 104,28 |

| Cable     |   |        |
|-----------|---|--------|
| 1510-302B | Hybrid cable, black (Power and AES/EBU), 50m reels  | 323,90 |
| 1550-105  | Loom 5m, with DB 25 pin male and 8 pcs. XLR female connectors, providing AD9200A connectivity to 8 pcs. XLR balanced monitor outputs. | 281,24 |